

HARDOX® 500 Tuf PLATE

2024-09-18

HARDOX® 500 Tuf SHEET

The table shows available dimensions in mm for direct order including the maximum length

The table shows available dimensions in mm for direct order including maximum length
Cut lengths with mill edges, black

Some restrictions, contact your local sales representative for information
Outside the range of dimensions

Minimum length: 2000 mm*)
Minimum quantities:
Thickness: 3.0 - 38.1mm
Min. position weight: 2.5 tons

Some restrictions, please contact product manager or Tech support
Outside the range of dimensions
Min. length 1500 mm
Min. bundle weight 2 ton

Width	1000-	1351-	1500-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-	
Thickness	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.0 - 3.9																						
4.0 - 4.7																						
4.8 - 5.7																						
5.8 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 24.0																						
24.1 - 25.0																						
25.1 - 26.0																						
26.1 - 27.0	14000																			14200	14400	
27.1 - 28.0	13400																			14200	13700	13800
28.1 - 29.0	13000																		14100	13700	13300	12900
29.1 - 30.0	12500																		14100	13600	13200	12800
30.1 - 31.0	12100																		14100	13600	13200	12800
31.1 - 32.0	11800																		14100	13600	13200	12800
32.1 - 33.0	11400																		14200	13700	13300	12900
33.1 - 34.0	11100																		14200	13700	13300	12900
34.1 - 35.0	10700																		14200	13700	13300	12900
35.1 - 36.0	10400																		14100	13600	13200	12800
36.1 - 37.0	10200																		14100	13600	13200	12800
37.1 - 38.1	9900																		14100	13600	13200	12800
38.2 - 39.0																			14100	13600	13200	12800
39.1 - 40.0																			14100	13600	13200	12800
40.1 - 45.0																			14100	13600	13200	12800
45.1 - 50.0																			14100	13600	13200	12800
50.1 - 51.0																			14100	13600	13200	12800
51.1 - 60.0																			14100	13600	13200	12800
60.1 - 65.0																			14100	13600	13200	12800
65.1 - 70.0																			14100	13600	13200	12800
70.1 - 75.0																			14100	13600	13200	12800
75.1 - 100.0																			14100	13600	13200	12800

Width	950-	1001-	1201-	1251-	1301-	1501-	1531-	1551-	1576-	1601-	1626-
Thickness	1000	1200	1250	1300	1500	1530	1550	1575	1600	1625	1650
2.00 - 2.49											
2.50 - 2.99											
3.00 - 3.09											
3.10 - 3.19											
3.20 - 3.49											
3.50 - 4.49											
4.50 - 4.79											
4.80 - 4.99											
5.00 - 6.00											
6.01 - 6.40											
6.41 - 6.50											
6.51 - 7.00											
7.01 - 8.00											
8.01 - 10.0											
10.1 - 25.0											
25.1 - 26.0											
26.1 - 27.0											

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.

*) Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.

