

# HARDOX® 400 PLATE

2018-06-19

# HARDOX® 400 SHEET

The table shows available dimensions in mm for direct order including the maximum length.

The table shows available dimensions mm for direct order including maximum length.  
Cut lengths with mill edges, black

Some restrictions, contact your local sales representative for more information

Some restrictions on dimensions and minimum quantities, contact your sales representative for more information

Minimum length: 2000 mm  
Minimum quantities:

Thickness: Min. position weight:  
4.0-60.0 2.5 tons  
60.1-100.0 3.5 tons  
100.1-120.0 4.0 tons  
120.1- 5.0 tons

Outside the range of dimensions

Some restrictions, please contact product manager or Tech support.  
techsupport@ssab.com

Outside the range of dimensions

Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by product manager Haradox®.  
For thermally cut edges, contact local sales force

Min. length 1500 mm  
Min. bundle weight 2 tons

Width Thickness	1000-1350	1351-1500	1501-1600	1601-1700	1701-1800	1801-1900	1901-2000	2001-2100	2101-2200	2201-2300	2301-2400	2401-2500	2501-2600	2601-2700	2701-2750	2751-2800	2801-2900	2901-3000	3001-3100	3101-3200	3201-3300	3301-3350	
3.2-3.9																							
4.0-4.7																							
5.8-6.0																							
6.1-6.7																							
6.8-7.7																							
7.8-8.7																							
8.8-10.0																							
10.1-25.0																							
25.1-26.0																							
26.1-27.0																							
27.1-28.0																							
28.1-29.0																							
29.1-30.0																							
30.1-31.0																							
31.1-32.0																							
32.1-33.0	14200																						
33.1-34.0	13800																						
34.1-35.0	13400																						
35.1-36.0	13100																						
36.1-37.0	12700																						
37.1-38.0	12400																						
38.1-39.0	12000																						
39.1-40.0	11700																						
40.1-45.0	10400																						
45.1-50.0	9400																						
50.1-55.0	9000	14400																					
55.1-60.0	8600	14100	13200	12800	12400	12000	11600	11200	10800	10400	10000	9600	9200	8800	8400	8000	7600	7200	6800	6400	6000	5600	
60.1-65.0	7900	13000	11200	10800	10400	10000	9600	9200	8800	8400	8000	7600	7200	6800	6400	6000	5600	5200	4800	4400	4000	3600	
65.1-70.0	7300	12100	11200	10700	10100	9500	9000	8400	7800	7200	6600	6000	5400	4800	4200	3600	3000	2400	1800	1200	600		
70.1-75.0	6800	11300	10600	10000	9400	8800	8200	7600	7000	6400	5800	5200	4600	4000	3400	2800	2200	1600	1000	400			
75.1-80.0	6300	10600	9900	10000	9400	8800	8200	7600	7000	6400	5800	5200	4600	4000	3400	2800	2200	1600	1000	400			
80.1-85.0	5900	9900	9300	10000	8800	8400	8000	7600	7200	6800	6400	6000	5600	5200	4800	4400	4000	3600	3200	2800	2400	2000	
85.1-90.0	5500	9400	9000	8400	8300	7900	7500	7100	6700	6300	5900	5500	5100	4700	4300	3900	3500	3100	2700	2300	1900	1500	
90.1-95.0	5200	9000	8800	8900	7900	7900	7400	6900	6400	5900	5400	4900	4400	3900	3400	2900	2400	1900	1400	900	400		
95.1-100.0	4900	8500	8300	8500	7500	7400	7000	6500	6000	5500	5000	4500	4000	3500	3000	2500	2000	1500	1000	500			
100.1-105.0	4700	8400	7900	8000	7100	7100	6700	6200	5700	5200	4700	4200	3700	3200	2700	2200	1700	1200	700				
105.1-110.0	4400	8000	7500	7700	6800	6700	6400	6000	5600	5200	4800	4400	4000	3600	3200	2800	2400	2000	1600	1200	800	400	
110.1-115.0	4200	7600	7200	7300	6500	6400	6100	5800	5500	5200	4800	4500	4200	3900	3600	3300	3000	2700	2400	2100	1800	1500	
115.1-120.0	4000	7300	6800	7000	6200	6100	5800	5500	5200	4800	4500	4200	3900	3600	3300	3000	2700	2400	2100	1800	1500	1200	
120.1-125.0	3800	7000	6600	6800	5900	5800	5500	5200	4800	4500	4200	3900	3600	3300	3000	2700	2400	2100	1800	1500	1200	900	
125.1-130.0	3700	6700	6300	6500	5700	5600	5300	5000	4600	4300	4000	3700	3400	3100	2800	2500	2200	1900	1600	1300	1000	700	
130.1-135.0																							
135.1-140.0																							

Maximum length 16 000 mm

Min. position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.  
Delivery weight accuracy +/- 10 %, at least - 2 tons / + 3 tons.

