

HARDOX® 400 PLATE

2018-01-12

HARDOX® 400 SHEET

The table shows available dimensions in mm for direct order including the maximum length.

Some restrictions, contact your local sales representative for more information

Some restrictions on dimensions and minimum quantities, contact your sales representative for more information

Outside the range of dimensions

Only 1650 mm width, mill edges - 0/+70 mm. Other dimensions must be approved by product manager Haradox®. For thermally cut edges, contact local sales force

The table shows available dimensions mm for direct order including maximum length. Cut lengths with mill edges, black

Some restrictions, please contact product manager or Tech support, techsupport@ssab.com

Outside the range of dimensions

Min. length 1500 mm
Min. bundle weight 2 tons

Width Thickness	1000-1350-1350	1500-1500	1600-1600	1700-1700	1800-1800	1900-1900	2000-2000	2100-2100	2200-2200	2300-2300	2400-2400	2500-2500	2600-2600	2700-2700	2800-2800	2900-2900	3000-3000	3100-3100	3200-3200	3300-3300	3350-3350	
3.2 - 3.9																						
4.0 - 4.7																						
4.8 - 5.7																						
5.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						
26.1 - 27.0																						
27.1 - 28.0																						
28.1 - 29.0																						
29.1 - 30.0																						
30.1 - 31.0																						
31.1 - 32.0																						
32.1 - 33.0																						
33.1 - 34.0																						
34.1 - 35.0																						
35.1 - 36.0																						
36.1 - 37.0																						
37.1 - 38.0																						
38.1 - 39.0																						
39.1 - 40.0																						
40.1 - 45.0																						
45.1 - 50.0																						
50.1 - 55.0																						
55.1 - 60.0																						
60.1 - 65.0																						
65.1 - 70.0																						
70.1 - 75.0																						
75.1 - 80.0																						
80.1 - 85.0																						
85.1 - 90.0																						
90.1 - 95.0																						
95.1 - 100.0																						
100.1 - 105.0																						
105.1 - 110.0																						
110.1 - 115.0																						
115.1 - 120.0																						
120.1 - 125.0																						
125.1 - 130.0																						
130.1 - 135.0																						
135.1 - 140.0																						

Width Thickness	950-1000	1000-1200	1200-1250	1250-1300	1300-1500	1500-1525	1525-1550	1550-1575	1575-1600	1600-1625	1625-1650
2.00 - 2.49											
2.50 - 2.99											
3.00 - 3.19											
3.20 - 3.49											
3.50 - 3.99											
4.00 - 4.49											
4.50 - 4.79											
4.80 - 4.99											
5.00 - 5.99											
6.00 - 6.40											
6.41 - 6.50											
6.51 - 6.99											
7.00 - 8.00											
8.10 - 10.0											
10.1 - 25.0											
25.1 - 26.0											
26.1 - 27.0											

Minimum length 2000 mm
Minimum quantities:
4.0-60.0 2.5 tons
60.1-100.0 3.5 tons
100.1-120.0 4.0 tons
120.1- 5.0 tons

Minimum length 14630 mm

Minimum weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width. Delivery weight accuracy +/- 10 %, at least - 2 tons / + 3 tons.