

HARDOX® 500 PLATE

2019-03-15

HARDOX® 500 SHEET

The table shows available dimensions in mm for direct order including the maximum length

- Some restrictions, contact your local sales representative for information
- Outside the range of dimensions
- Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by product manager Hardox®. For thermally cut edges, contact local sales force

Minimum length: 2000 mm
 Minimum quantities:
 Thickness: Min. position weight:
 3.0-60.0 2.5 tons
 60.1-100.0 3.5 tons
 100.1-120.0 4.0 tons
 120.1- 5.0 tons

The table shows available dimensions in mm for direct order including maximum length

- Some restrictions, please contact product manager or Tech support, techsupport@ssab.com
 - Outside the range of dimensions
- Min. length 1500 mm
Min. bundle weight 2 ton

Width	1000-	1351-	1501-	1601-	1650	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-	
Thickness	1350	1500	1600	1700		1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.0 - 3.7																							
3.8 - 4.7																							
4.8 - 5.7																							
5.8 - 6.7																							
6.8 - 7.7																							
7.8 - 8.7																							
8.8 - 10.0																							
10.1 - 24.0																							
24.1 - 25.0																							
25.1 - 26.0																							14400
26.1 - 27.0	14000																					14200	
27.1 - 28.0	13400																					14200	13700
28.1 - 29.0	13000																					14100	13300
29.1 - 30.0	12500																					14100	12900
30.1 - 31.0	12100																					14100	12000
31.1 - 32.0	11800																					14200	11700
32.1 - 33.0	11400																					14200	11300
33.1 - 34.0	11100																					14400	11000
34.1 - 35.0	10700																					13900	10700
35.1 - 36.0	10400																					14100	10500
36.1 - 37.0	10200																					14300	10200
37.1 - 38.0	9900																					13900	10000
38.1 - 39.0	9600																					14200	9700
39.1 - 40.0	9400																					14400	9500
40.1 - 45.0	8300																					14100	8400
45.1 - 50.0	7500	13500	13500	13500		13500	13400	12700	12100	11500	11000	10600	10100	9700	9400	9000	8700	8400	8200	7900	7700	7600	7600
50.1 - 55.0	6800	11200	11200	11200		11200	11200	11200	11000	10500	10000	9600	9200	8900	8500	8200	7900	7700	7400	7200	7000	6900	6900
55.1 - 60.0	7800	11200	11200	11200		11200	11100	10600	10100	9600	9200	8800	8400	8100	7800	7500	7300	7000	6800	6600	6400	6300	6300
60.1 - 65.0	7200	11200	11200	11200		10800	10300	9700	9300	8900	8500	8100	7800	7500	7200	6900	6700	6500	6300				
65.1 - 70.0	6700	10800	10800	10700	12100	10100	9500	9000	8600	8200	7900	7500	7200	6900	6700	6400	6200						
70.1 - 75.0	6200	10100	10100	10000	11300	9400	8900	8400	8000	7700	7300	7000	6700	6500	6200								
75.1 - 80.0	5900	9400	9400	9400	10600	8800	8300	7900	7500	7200	6900	6600	6300										
80.1 - 100.0	8400	8400	7900	7500	8500	7100	6700	6400	6100	5800													
100.1 - 103.0	8400	8400	7900	7100	8000	7100	6700	6400	6100	5800													
103.1 - 115.0																							
115.1 - 130.0																							
130.1 - 150.0																							

Width	950-	1001-	1201-	1251-	1301-	1501-	1526-	1551-	1576-	1601-	1626-	1650-
Thickness	1000	1200	1250	1300	1500	1525	1550	1575	1600	1625	1650	
2.00 - 2.49												
2.50 - 2.99												
3.00 - 3.09												
3.10 - 3.19												
3.20 - 3.99												
4.00 - 4.49												
4.50 - 4.79												
4.80 - 4.99												
5.00 - 5.99												
6.00 - 6.40												
6.41 - 6.50												
6.51 - 7.00												
7.10 - 8.00												
8.10 - 10.0												
10.1 - 25.0												
25.1 - 26.0												
26.1 - 27.0												

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
 Delivery weight accuracy +/- 10 %, at least -2 tons / +3 tons.

