

HARDOX® 600 PLATE

2020-05-05

The table shows available dimensions for direct order including the maximum length (mm)

Minimum length: 2000 mm

- Some restrictions on dimensions, contact your local sales representative for information
- Some restrictions on dimensions and quantities, contact your local sales representative for information
- Outside the range of dimension

- Min quantities: Min position weight:
- Thickness: weight:
- 3.0 - 60.0 2.5 tons
- 60.1 - 100.0 3.5 tons
- 100.1 - 120.0 4.0 tons
- 120.1 - 5.0 tons

Width (mm)	1000-	1351-	1500-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-
Thickness (mm)	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000
3.0-3.7*																	
3.8-4.7*																	
4.8-5.9*																	
6.0-6.7																	
6.8-7.9																	
8.0-8.7																	
8.8-13																	
13.1-24																	
24.1-25																	
25.1-26																	
26.1-27	14000																
27.1-28	13400																
28.1-29	13000																
29.1-30	12500																
30.1-31	12100																
31.1-32	11800																
32.1-33	11400																
33.1-34	11100																
34.1-35	10700																
35.1-36	10400																
36.1-37	10200																
37.1-38	9900																
38.1-39	9600																
39.1-40	9400																
40.1-45	8300																14100
45.1-50	7500	13500	13500	13500	13500	13400	12700										
50.1-51	6800	11200	11200	11200	11200	11200	11200										
51.1-60	7800	11200	11200	11200	11200	11200	10600										
60.1-65	7200	11200	11200	11200	10800	10300	9700										
65.1-70																	
70.1-75																	
75.1-80																	
80.1-102																	
102.1-115																	
115.1-130																	
130.1-150																	

HARDOX® 600 SHEET

The table shows available dimensions in mm for direct order including maximum length
Cut lengths with mill edges, black

- Some restrictions on dimensions, contact your local sales representative for information
- Thickness 5.01-6.00 are still under development (Trial Delivery Phase). Preferred dimensions are 1500 x 3000 mm. For more information, Please contact Tech support, techsupport@ssab.com
- Outside the range of dimensions

Width (mm)	870-	950-	1001-	1201-	1251-	1301-	1351-	1401-	1511-	1576-	1601-	1626-
Thickness (mm)	949	1000	1200	1250	1300	1350	1400	1510	1575	1600	1625	1650
2.00 - 2.49												
2.50 - 2.99												
3.00 - 3.49												
3.50 - 3.99												
4.00 - 4.50												
4.51 - 4.79												
4.80 - 5.00												
5.01 - 6.00												
6.01 - 6.30												
6.41 - 6.50												
6.51 - 7.00												
7.10 - 8.00												
8.10 - 10.0												
10.1 - 25.0												
25.1 - 26.0												
26.1 - 27.0												

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.

Min. length 1500 mm
Min. bundle weight 2 ton