

HARDOX® 500 Tuf PLATE

2020-06-24

HARDOX® 500 Tuf SHEET

The table shows available dimensions in mm for direct order including the maximum length

The table shows available dimensions in mm for direct order including maximum length
Cut lengths with mill edges, black

- Some restrictions, contact your local sales representative for information
- Outside the range of dimensions

Minimum length: 2000 mm
 Minimum quantities:
 Thickness: Min. position weight:
 3.0-60.0 2.5 tons
 60.1-100.0 3.5 tons
 100.1-120.0 4.0 tons
 120.1- 5.0 tons

- Some restrictions, please contact product manager or Tech support, techsupport@ssab.com
 - Outside the range of dimensions
- Min. length 1500 mm
Min. bundle weight 2 ton

Width	1000-	1351-	1500-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-	
Thickness	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.0 - 3.7																						
3.8 - 4.7																						
4.8 - 5.7																						
5.8 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 24.0																						
24.1 - 25.4																						
25.5 - 26.0																						
26.1 - 27.0																						
27.1 - 28.0																						
28.1 - 29.0																						
29.1 - 30.0																						
30.1 - 31.0																						
31.1 - 32.0																						
32.1 - 33.0																						
33.1 - 34.0																						
34.1 - 35.0																						

Width	950-	1001-	1201-	1251-	1301-	1501-	1526-	1551-	1576-	1601-	1626-
Thickness	1000	1200	1250	1300	1500	1525	1550	1575	1600	1625	1650
2.00 - 2.49											
2.50 - 2.99											
3.00 - 3.09											
3.10 - 3.19											
3.20 - 3.99											
4.00 - 4.49											
4.50 - 4.79											
4.80 - 4.99											
5.00 - 5.99											
6.00 - 6.40											
6.41 - 6.50											
6.51 - 7.00											
7.10 - 8.00											
8.10 - 10.0											
10.1 - 25.0											
25.1 - 26.0											
26.1 - 27.0											

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
 Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.

