

The table shows available dimensions in mm for direct order including the maximum length.

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

Minimum length: 2000 mm

Minimum quantities:

Minimum position weight:

3.0-60.0 2.5 tons

60.1-100.0 3.5 tons

100.1-120.0 4.0 tons

120.1- 5.0 tons

Width	1000-1350	1350-1500	1500-1600	1600-1700	1700-1800	1800-1900	1900-2000	2000-2100	2100-2200	2200-2300	2300-2400	2400-2500	2500-2600	2600-2700	2700-2800	2800-2900	2900-3000	3000-3100	3100-3200	3200-3300	3300-3350	
Thickness																						
3.2 - 3.9																						
4.0 - 4.6																						
4.7 - 5.7																						
5.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						
26.1 - 27.0																						
27.1 - 28.0																						
28.1 - 29.0																						
29.1 - 30.0																						
30.1 - 31.0																						
31.1 - 32.0																						
32.1 - 33.0	14200																					14600
33.1 - 34.0	13800																					14000
34.1 - 35.0	13400																					13500
35.1 - 36.0	13100																					13100
36.1 - 37.0	12700																					12600
37.1 - 38.0	12400																					12200
38.1 - 39.0	12000																					11800
39.1 - 40.0	11700																					11500
40.1 - 45.0	10400																					11100
45.1 - 50.0	9400																					10200
50.1 - 51.0	9000		14400	13600	12800	12100	11500	11000	10500	10000	9600	9200	9000	9000	9000	8700	8400	8200	7900	7700	7000	6900
51.1 - 60.0																						
60.1 - 65.0																						
65.1 - 70.0																						
70.1 - 75.0																						
75.1 - 80.0																						
80.1 - 102.0																						
102.1 - 115.0																						
115.1 - 130.0																						
130.1 - 150.0																						