



The table shows available dimensions in mm for direct order including the maximum length.

Minimum length: 2000 mm

Minimum quantities:

Thickness:	Minimum position weight:
3.0-60.0	2.5 tons
60.1-100.0	3.5 tons
100.1-120.0	4.0 tons
120.1-	5.0 tons

 Some restrictions, contact your local sales representative for more information

 Outside the range of dimensions

Width	1000-	1351-	1501-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-	
Thickness	1350	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.2 - 3.9																						
4.0 - 4.6																						
4.7 - 5.7																						
5.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						14600
26.1 - 27.0																					14200	14000
27.1 - 28.0																				14200	13700	13500
28.1 - 29.0																			14100	13700	13300	13100
29.1 - 30.0																		14100	13600	13200	12800	12600
30.1 - 31.0																	14100	13600	13200	12800	12400	12200
31.1 - 32.0				Maximum length 14630 mm												14200	13700	13200	12800	12400	12000	11800
32.1 - 33.0	14200																					
33.1 - 34.0	13800												14400	13800	13300	12900	12400	12000	11700	11300	11100	
34.1 - 35.0	13400											14500	13900	13400	12900	12500	12100	11700	11300	11000	10800	
35.1 - 36.0	13100											14100	13600	13100	12600	12200	11700	11400	11000	10700	10500	
36.1 - 37.0	12700											14300	13700	13200	12700	12200	11800	11400	11100	10700	10200	
37.1 - 38.0	12400											14500	13900	13400	12800	12400	11900	11500	11100	10800	10400	10000
38.1 - 39.0	12000											14200	13600	13000	12500	12000	11600	11200	10800	10500	10200	9700
39.1 - 40.0	11700											14400	13800	13200	12700	12200	11700	11300	10900	10600	10200	9500
40.1 - 45.0	10400											14100	13400	12800	12300	11700	11300	10800	10400	10100	9700	8400
45.1 - 50.0	9400											14100	13400	12700	12100	11500	11000	10600	10100	9700	9400	7600
50.1 - 51.0	9000											14400	13600	12900	12300	11700	11100	10600	10100	9700	9000	6900
51.1 - 60.0																						
60.1 - 65.0																						
65.1 - 70.0																						
70.1 - 75.0																						
75.1 - 80.0																						
80.1 - 102.0																						
102.1 - 115.0																						
115.1 - 130.0																						
130.1 - 150.0																						