

The table shows available dimensions for direct order including the maximum length (mm)

Some restrictions, contact your local sales representative for more information

Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by Product Manager Strenx

For thermally cut edges, contact local sales force

Outside the range of dimensions

Minimum length: 2000 mm

Minimum quantities:

Thickness: Minimum position weight:

4.0 - 60.0 2.5 tons

60.1 - 100.0 3.5 tons

Width (mm)	1000-	1350	1501	1650	1699	1700	1801	1901	2001	2101	2201	2301	2401	2501	2601	2701	2801	2901	3001	3101	3101	3200	3300	3301
Thickness (mm)	1350	1501	1650	1699	1700	1801	1901	2001	2101	2201	2301	2401	2501	2601	2701	2801	2901	3001	3101	3101	3200	3300	3301	
3.0 - 3.9																								
4.0 - 4.7																								
4.8 - 5.7																								
5.8 - 6.0																								
6.1 - 6.7																								
6.8 - 7.7																								
7.8 - 8.7																								
8.8 - 10.0																								
10.1 - 25.0																								
25.1 - 26.0																								
26.1 - 27.0																								
27.1 - 28.0																								
28.1 - 29.0																								
29.1 - 30.0																								
30.1 - 31.0																								
31.1 - 32.0																								
32.1 - 33.0	14200																							
33.1 - 34.0	13800																							
34.1 - 35.0	13400																							
35.1 - 36.0	13100																							
36.1 - 37.0	12700																							
37.1 - 38.0	12400																							
38.1 - 39.0	12000																							
39.1 - 40.0	11700																							
40.1 - 45.0	10400																							
45.1 - 50.0	9400																							
50.1 - 55.0	9000																							
55.1 - 60.0	8600																							
60.1 - 65.0	7900																							
65.1 - 70.0	7900																							
70.1 - 75.0	6800																							
75.1 - 80.0	6300																							
80.1 - 85.0	5900																							
85.1 - 90.0	5200																							
90.1 - 95.0	5200																							
95.1 - 100.0	4900																							
100.1 - 105.0																								
105.1 - 110.0																								
110.1 - 115.0																								
115.1 - 120.0																								
120.1 - 125.0																								
125.1 - 130.0																								
130.1 - 135.0																								
135.1 - 140.0																								