

The table shows available dimensions for direct order including the maximum length (mm)

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

Minimum length: 2000 mm

Minimum quantities:

Thickness: Minimum position weight:

4.0-40.0 2.5 tons

Width (mm)	1000-	1350	1500	1501	1600	1699	1800	1700	1801	1900	1901	2000	2001	2100	2101	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3500	
Thickness (mm)																													
3.0 - 3.9																													
4.0 - 4.7																													
4.8 - 5.7																													
5.8 - 6.0																													
6.1 - 6.7																													
6.8 - 7.7																													
7.8 - 8.7																													
8.8 - 10.0																													
10.1 - 25.0																													
25.1 - 26.0																													
26.1 - 27.0																													
27.1 - 28.0																													
28.1 - 29.0																													
29.1 - 30.0																													
30.1 - 31.0																													
31.1 - 32.0																													
32.1 - 33.0																													
33.1 - 34.0																													
34.1 - 35.0																													
35.1 - 36.0																													
36.1 - 37.0																													
37.1 - 38.0																													
38.1 - 39.0																													
39.1 - 40.0																													
40.1 - 45.0																													
45.1 - 50.0																													
50.1 - 55.0																													
55.1 - 60.0																													
60.1 - 65.0																													
65.1 - 70.0																													
70.1 - 75.0																													
75.1 - 80.0																													