



**Declaration of Performance**  
(according Regulation EU No 305/2011)

No. Strip S235J0 016

**Strip/CTL S235J0 / 1.0114 according to EN 10025-2**

Produced by SSAB manufacturing plant Borlänge

To be used in-welded, bolted and riveted structures

SSAB  
P.O Box 70  
101 20 Stockholm  
SWEDEN  
T: +46 8 45 45 700  
Email: info@ssab.com  
Webbbsite: ssab.com

TÜV NORD Systems GmbH & Co. KG  
Große Bahnstraße 31  
D-22525 Hamburg  
Germany  
T: +49 40 8557 2368

System of assessment and verification of constancy of performance of the product

**System 2+**

Notified factory production control certification body

No. 0045 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

Charlotta Jansson

2017-09-01

Quality Manager

Essential characteristics		Performance			Harmonised technical specification	
Tolerances on dimensions and shape (EN 10051)	Nominal thickness (t)		Nominal width (w)			EN 10025-1:2004
	mm	t ≤ 2.00	w ≤ 1200	1200 < w ≤ 1500	1500 < w ≤ 1600	
	mm	2.00 < t ≤ 2.50	± 0.17	± 0.19	± 0.21	
	mm	2.50 < t ≤ 3.00	± 0.18	± 0.21	± 0.23	
	mm	3.00 < t ≤ 4.00	± 0.20	± 0.22	± 0.24	
	mm	4.00 < t ≤ 5.00	± 0.22	± 0.24	± 0.26	
	mm	5.00 < t ≤ 6.00	± 0.24	± 0.26	± 0.28	
	mm	6.00 < t ≤ 8.00	± 0.26	± 0.28	± 0.29	
	mm	8.00 < t ≤ 10.00	± 0.29	± 0.30	± 0.31	
	mm	10.00 < t ≤ 12.50	± 0.32	± 0.33	± 0.34	
	mm	12.50 < t ≤ 15.00	± 0.35	± 0.36	± 0.37	
mm	15.00 < t ≤ 16.00	± 0.37	± 0.38	± 0.40		
mm	15.00 < t ≤ 16.00	± 0.40	± 0.42	± 0.45		
Yield strength	min (MPa)		235			
Tensile strength	(MPa)		360 - 510			
Elongation	Nominal thickness (t)		min (%)			
	mm	1.8 ≤ t ≤ 2	17			
	mm	2 < t ≤ 2.5	18			
	mm	2.5 < t < 3	19			
mm	3 ≤ t ≤ 16	24				
Impact strength	min ( J/°C)		27/0			
Weldability CEV	max (%)		0.35			
Durability						
C	max (%)		0.17			
Si	max (%)		NDP			
Mn	max (%)		1.40			
P	max (%)		0.030			
S	max (%)		0.030			
Cu	max (%)		0.55			



**10**

**0045-CPR-2028**

[www.ssab.com/downloads](http://www.ssab.com/downloads)