



**Declaration of Performance**

(according Regulation EU No 305/2011)

No. Strip S890QL 020

**Strip/CTL S890QL / 1.8983 according to EN 10025-6**

Produced by SSAB manufacturing plant Borlänge

To be used in-welded, bolted and riveted structures

SSAB  
P.O Box 70  
101 20 Stockholm  
SWEDEN  
T: +46 8 45 45 700  
Email: info@ssab.com  
Webbsite: ssab.com

TÜV NORD Systems GmbH & Co. KG  
Große Bahnstraße 31  
D-22525 Hamburg  
Germany  
T: +49 40 8557 2368

System of assessment and verification of constancy of performance of the product

**System 2+**

Notified factory production control certification body No. 0045 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

Charlotta Jansson

2017-09-01

Quality Manager

Essential characteristics		Performance			Harmonised technical specification	
Tolerances on dimensions and shape (EN 10051)		Nominal width (mm)			EN 10025-1:2004	
	Nominal thickness (mm)	w≤1200	1200<w≤1500	1500<w≤1600		
	mm	t ≤ 2.00	± 0.17	± 0.19		± 0.21
	mm	2.00 <t≤ 2.50	± 0.18	± 0.21		± 0.23
	mm	2.50 <t≤ 3.00	± 0.20	± 0.22		± 0.24
	mm	3.00 <t≤ 4.00	± 0.22	± 0.24		± 0.26
	mm	4.00 <t≤ 5.00	± 0.24	± 0.26		± 0.28
	mm	5.00 <t≤ 6.00	± 0.26	± 0.28		± 0.29
	mm	6.00 <t≤ 8.00	± 0.29	± 0.30		± 0.31
	mm	8.00 <t≤ 10.00	± 0.32	± 0.33		± 0.34
	mm	10.00 <t≤ 12.50	± 0.35	± 0.36		± 0.37
	mm	12.50 <t≤ 15.00	± 0.37	± 0.38		± 0.40
mm	15.00 <t≤ 16.00	± 0.40	± 0.42	± 0.45		
Yield strength	min (MPa)	890				
Tensile strength	Nominal thickness (mm)	(Mpa)				
	mm	t ≥ 3	940 - 1100			
Elongation	Nominal thickness (mm)	min (%)				
	mm	3 ≤ t ≤ 16	11			
Impact strength	min (J/°C)	30/-40				
Weldability CEV	max (%)	0.72				
Durability						
C	max (%)	0.20				
Si	max (%)	0.80				
Mn	max (%)	1.70				
P	max (%)	0.020				
S	max (%)	0.010				
Cu	max (%)	0.50				



10

0045-CPR-2028

www.ssab.com/downloads